

WeatherMaster™ ULTIMATE MP SEALANT

To Whom It May Concern:

This letter has been sent to verify the compliance of Titebond® WeatherMaster™ Ultimate MP Sealant with the green building standard created by the National Association of Homebuilders (NAHB) and the International Code Council (ICC). This new consensus standard on green building is called the National Green Building Standard™ or ANSI ICC-700-2015.

According to the standard, Titebond® WeatherMaster Ultimate MP Sealant can be used to meet Section 901.10 of this standard

To qualify, a product must have a very low VOC and meet the SCAQMD Rule 1168 VOC limits specified in Table 901.10(3) of the standard.

This table lists a VOC limit for architectural sealants of 250 g/L.
Our product has a VOC content as follows:

The product as sold has a VOC of 0 g/L.

The reactive VOC of this product during cure is as follows:

For white and color versions, the reactive VOC is 18.2 g/L.

For the translucent version, the reactive VOC is 3 g/L.

For the crystal clear version, the reactive VOC is 11 g/L.

This statement is based upon the current formulation of the product and the regulations in place at the time of this letter.

By using Titebond® WeatherMaster Ultimate MP Sealant on your current green building project, you could be contributing up to five points under Section 901.10 of the National Green Building Standard.™

Please use this letter for specification purposes or call 1-888-533-9043 with further questions.
For a copy of the SDS or TDS, please visit www.Titebond.com

VISIT WWW.TITEBOND.COM FOR THE
MOST UP-TO-DATE PRODUCT INFORMATION



Franklin International

Columbus, Ohio 43207 614.443.0241 (Technical Service 1.800.347.4583)

© 2019 01421-3944_LB