

ULTIMATE MP™ TEXTURED SEALANT



Titebond® WeatherMaster® ULTIMATE MP™ Textured Sealant is an elastic moisture curing sealant with a textured consistency perfect for use on asphalt, stucco, concrete, mortar, wood, brick, concrete and stone. It can be extruded in extreme temperatures with a unique polyether chemistry to eliminate out-gassing on green concrete and protect against discoloration when exposed to ultraviolet light.

Ultimate performance. Ultimate results.
ULTIMATE MP TEXTURED SEALANT.

Ready to Use

No mixing or primer required;
reduces labor and installation cost

Ultra Low VOC

VOC-compliant in all 50 states

Joint Movement Capability ± 35%

Remains permanently flexible

Textured Look

Perfect for stucco, concrete, brick and more!

Paintable

May be painted one hour after application

Wide Temperature Application Range

Suitable for all climates

Ideal Applications Include:

- Windows & Doors
- Siding
- Curtain Walls
- Roofs
- Fiberglass
- Vinyl siding
- RV, tractor trailers & buses where textured look is needed

MULTI-PURPOSE

ULTIMATE MP™ TEXTURED SEALANT

SPECIFICATIONS

- ASTM C920, Type S, Grade NS, Class 35, Uses NT, M, G, A & O
- Federal Specification TT-S-00230-C Type II, Class A
- Corps of Engineers CRD-C-541, Type II, Class A
- Canadian Standards Board CAN 19, 13-M82
- AAMA 802.3-08 Type II, AAMA 803.3-08 Type I, and AAMA 805.2-08 Group C

PHYSICAL AND CHEMICAL CHARACTERISTICS

Type: Advanced polymer **Paintable:** After 1 hour

Reactive VOC: 0 g/L; 29.1g/L **Tack-free time:** 1 hour
(2.23%) during cure

Tooling time: 10-15 minutes **Shore A:** 20-30

Full cure: 24 hours **Solids:** 97.77%

Weight per gallon: 10.9 lbs.

Freeze thaw stability: Stable

Flashpoint: Solvent free/Not applicable

Application temperature: Above 0° F (-18° C)

Joint movement capability: ± 35%

Storage life: 18 months

Coverage: Provides about 31 linear feet at a 1/4" bead

Clean-up: Uncured material may be cleaned with isopropyl alcohol or acetone. After curing, excess sealant must be cut or scraped away. Follow solvent vendor's precautions when using solvents.

Limited Warranty: If not satisfied with product performance when used as directed, return container and proof of purchase to Franklin International, Inc. for replacement of product. Buyer's sole remedy shall be limited only to the replacement of product exclusive of cost of labor. No other warranties are expressed or implied.

APPLICATION

Titebond WeatherMaster ULTIMATE MP textured sealant comes ready to use. Apply by professional cartridge gun. Extrude sealant into openings, gaps, or holes surrounding the application. Fill joint opening to maximum capacity and repeat as necessary. Always apply sealant in a bead form. If joint depth exceeds ½", use backing material. To ensure neat sealant lines, mask areas adjacent to joints. Once sealant is dry to the touch and does not transfer, remove masking tape. Painting may occur one hour after application with a water-based (latex-based) paint. For other paint types, a compatibility test is recommended.

LIMITATIONS

- ULTIMATE MP textured sealant is intended for exterior use.
- Air, sealant and surface temperature should be above 0° F (-18° C).
- Once sealant is applied, do not wipe with solvents.
- Always apply sealant in a bead form.
- If joint depth exceeds 1/2", use backing material.
- Not designed for continuous submersion or use below the waterline.

For questions, please call our Help Line 1.800.347.4583 or visit us at Titebond.com.

CAUTION STATEMENT

CAUTION: EYE AND SKIN IRRITANT. Do not swallow. Do not allow eye contact or prolonged skin contact. **First Aid:** If swallowed, do not induce vomiting; contact physician. If eye contact occurs, flush with water for 15 minutes. Wash skin contact areas with soap and water. If irritation from eye or skin contact areas persists, contact physician. For additional information, refer to Safety Data Sheet. **KEEP OUT OF THE REACH OF CHILDREN.**

Part Number	Size/Color	Weight	UPC	Units Per Package	Units Per Pallet
88001	10.1 oz Cartridge/White <i>6 colors available</i>	10.9 lbs.	0 37083 88001 4	12	108

Franklin International

Sales: 1.800.669.4583 / Technical: 1.800.347.4583

©2017 FF1051

TITEBOND.COM

