

Designed for Interior & Exterior Use

EXCEEDS
ASTM C920
CLASS 25

PRO-GRADE+ Caulk

Repair, Seal & Fill / Dries Quickly / Paintable in 2 Hours

Titebond® Pro-Grade Plus Caulk is a multi-purpose, siliconized acrylic latex caulk for interior and exterior use. This easy-to-use formula dries quickly, will not cause shiners and cleans up with water. It offers great weather resistance, a water-resistant seal once cured, tools easily, and can be painted in 2 hours. It contains no plasticizers or phthalates and offers unbeatable adhesion to most common building materials including wood, metal, glass, tile and more.

50 YEAR WARRANTY

Ideal For

Interior & Exterior Applications Like: Sealing Joints / Repairing Cracks / Back-filling Gaps

Seals

Wood / Metal / Glass / Tile / Drywall / Plaster / Concrete / Plastic / Fiberglass / Masonry / Aluminum / Brick / Most Common Building Materials

Ultra Low VOC

VOC-compliant in all 50 states

Easy to Use


Tools easily, cleans up with water

Paintable

May be painted with a water-based (latex) paint that does not contain plasticizer 2-4 hours after application

Wide Temperature Application Range

40°F - 120°F



Titebond®
THE PRO'S ADVANTAGE

Ordering/Sku Information

Size/Color	Part Number	UPC	Case UPC	Weight	Units Per Package	Packages Per Pallet
10.1 Oz. Cartridge / White	8401	037083084016	10037083084013	13.8 lbs.	12	108

Physical & Chemical Properties

- **Type:** Siliconized acrylic
- **Calculated VOC:** <1.5%
- **Tooling time:** 10-15 minutes
- **Full cure:** 3-7 days*
- **Freeze thaw stability:** Stable
- **Flashpoint:** Solvent free/Not applicable
- **Application temperature:** Above 40°F (4°C)
- **Joint movement capability:** ± 25%
- **Storage life:** 24 months in a dry location at or below 75°F
- **Coverage:** 31 linear ft. at a 1/4" bead
- **Paintable:** 2-4 hours
- **Tack-free time:** 20 minutes
- **Solids:** 80%
- **Cleanup:** Clean uncured material with water. After curing, excess sealant must be cut or scraped away.

* Cure will be affected by joint size, configuration and environmental conditions.

Specifications

Complies with the following requirements:

- ASTM C834 Type OP Grade -18°C
- ASTM C920 Type S Grade NS Class 25

Application

Titebond® Pro-Grade Plus Caulk comes ready to use. Surfaces must be clean and free of any material that may prevent adequate adhesion. Properly designed joint not to exceed 1/2" in depth. Cut tip at 45° angle for 1/8" to 1/2" bead and place in professional cartridge gun. Apply caulk into clean joint. If necessary, smooth bead immediately. It is the sole responsibility of the user to thoroughly test any proposed use with all substrates to determine project suitability.

Limitations

Not designed for continuous submersion or use below the waterline. Air, caulk and surface temperature should be above 40°F. Do not apply if rain is expected within 12 hours. Cure time is dependent upon ambient conditions including temperature and humidity. The caulk should be dry to the touch and ready to paint in 2-4 hours with a water-based (latex) paint that does not contain plasticizer. For other paint types, a compatibility test is recommended. It is highly recommended to use backing material. For best results, store in a dry location at or below 75°F. For questions, please call our Help Line at 1.800.347.4583 or visit us at Titebond.com.

50 Year Limited Warranty: If not satisfied with product performance when used as directed, return container and proof of purchase to Franklin International, Inc. for replacement of product. Liability is limited to product replacement only.

Visit Titebond.com for the most up-to-date product information.

Franklin International



Columbus, Ohio 43207 614.443.0241 Technical Service 1.800.347.4583 © 2022 01504_5699LN FF1245

