

KITCHEN & BATH SEALANT



Titebond® Kitchen & Bath Sealant is a modified acrylic formula specifically designed to permanently seal high-moisture areas found in kitchens and baths. It is ideal for sealing around tubs, showers, sinks and countertops and offers excellent adhesion to many common materials including vinyl, ceramic tile, aluminum, glass, marble, brick, wood, porcelain, plastic and painted surfaces. This flexible, mildew-resistant sealant offers strong, watertight adhesion and will not discolor over time. When fully cured, Kitchen & Bath is safe for food preparation areas and offers a durable water, humidity and stain resistant seal.

Ready to Use

No mixing or primer required;
reduces labor and installation cost

Ultra Low VOC

VOC-compliant in all 50 states

Joint Movement

Remains flexible

Weather Resistant

Produces long-lasting weather-tight seals

Paintable

May be painted with premium grade water-based
paints 2-4 hours after application

Wide Temperature Application Range

40°F – 120°F

Ideal Applications Include:

- Baths
- Tubs
- Sinks
- Countertops

INTERIOR

KITCHEN & BATH

SPECIFICATIONS

Complies with the following requirements:

- ASTM C-834 Type OP Grade 0°C (Type C Grade NF for Clear)
- FDA 21-CFR-177.2600

PHYSICAL AND CHEMICAL CHARACTERISTICS

Type: Modified Acrylic	Paintable: 2-4 hours
Non-reactive VOC: White & Almond: 20 g/L (< 1.5% wt.)	Solids: Colors: 72% Clear: 60%
Clear: 5 g/L (< 0.8%)	
Tack-free time: 2-3 hours	
Tooling time: 15 minutes	
Full cure: 3-7 days*	
Weight per gallon: White & Almond: 11.23 lbs. / Clear: 8.8 lbs.	
Freeze thaw stability: Stable	
Flashpoint: Solvent free/Not applicable	
Application temperature: 40°F – 120°F	
Joint movement capability: Flexible	
Storage life: 24 months in tightly closed containers between 50°F to 80°F.	
Coverage: 10.1 fl. oz. = 31 linear ft. at a 1/4" bead	
Clean-up: Soap and water	

* Cure will be affected by joint size, configuration and environmental conditions.

50 Year Limited Warranty: If not satisfied with product performance when used as directed, return container and proof of purchase to Franklin International, Inc. for replacement of product. Liability is limited to product replacement only.

APPLICATION

Titebond® Kitchen & Bath Sealant comes ready to use. Apply by professional cartridge gun. Extrude sealant into openings, gaps or holes surrounding the application. Fill joint opening to maximum capacity and repeat as necessary. If joint depth exceeds 1/2", use backing material. If necessary, smooth bead immediately with a damp sponge. Painting may occur 2-4 hours after application with a premium grade water-based (latex-based) paint. For other paint types, a compatibility test is recommended. It is the sole responsibility of the user to thoroughly test any proposed use with all substrates to determine project suitability.

LIMITATIONS

Allow to dry at least 24 hours before exposing to water. Not designed for continuous submersion or use below the waterline. For questions, please call our Help Line at 1.800.347.4583 or visit us at Titebond.com. NOTE: Titebond Kitchen & Bath Clear (1711) will be white during application, but will turn clear within 7-14 days, depending on temperature, humidity and bead size.

CAUTION STATEMENT

WARNING: EYE, SKIN AND RESPIRATORY IRRITANT. The white & almond colors contain limestone, titanium dioxide and ethylene glycol. The clear color contains ethylene glycol. All products are harmful if swallowed. Long term exposure to ingredients in these products can increase the risk of certain cancers. Adverse reproductive effects have been reported in animals. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate personal protective equipment. **FIRST AID:** If swallowed, do not induce vomiting; contact physician. If eye contact occurs, flush eyes with water for 15-30 minutes; contact physician. Wash skin contact areas with soap and water; contact physician if irritation persists. For additional information, refer to Safety Data Sheet. **KEEP OUT OF THE REACH OF CHILDREN.**

WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects or other reproductive harm.

Part Number	Size/Color	Weight	UPC	Units Per Package	Units Per Pallet
1701	10.1 oz. Cartridge/White <i>3 colors available</i>	12.37 lbs.	037083017017	12	108

Franklin International

Sales: 1.800.669.4583 / Technical: 1.800.347.4583 ©2016 BCM 5/16 FF1014

TITEBOND.COM

